

# Capnography

Providing the ultimate sidestream performance along with cost-effective disposables



The ISA™ CO<sub>2</sub> module for the Root® patient monitoring and connectivity platform provides flexible applications across the continuum of care

- > Displays end-tidal carbon dioxide (EtCO<sub>2</sub>) waveform and measurements and trends of EtCO<sub>2</sub>, fractional concentration of inspired carbon dioxide (FiCO<sub>2</sub>), and respiration rate (RR)
- > Appropriate for monitoring infant, pediatric, or adult patients in a range of hospital environments including the OR, ICU, and medical-surgical units
- > Saves time in critical situations with virtually no warm-up time and full accuracy performance in ten seconds
- > Supports quiet environment initiatives with no disturbing pump noises
- > Generally requires 50 ml/minute sampling flow to support patient monitoring
- > External module enables easy movement for use on multiple Root monitors

Nomoline™—No moisture sampling lines and cannulas

- > Reduces disposable costs through:
  - Extended monitoring time in low- and high-humidity environments
  - Use of non-proprietary cannulas
- > Revolutionary design eliminates the need for a water trap
- > Patented polymer allows water in the sampling line to evaporate into the surrounding air, while leaving oxygen, carbon dioxide, and anesthetic gases unaffected
- > Hydrophobic bacterial filter protects ISA analyzers from water intrusion and cross-contamination



# FEATURES



> Root with capnography in Trend View



> Root with capnography in Analog View



> ISA™ CO2 module



MOC-9 ports



Nomline Airway Adapter Set for Intubated Patients



Nomline Adapter for Use with Non-Proprietary Cannulas

- > The portable ISA CO2 module easily mounts to the back of the Root patient monitoring platform and connects via Masimo Open Connect™ (MOC-9™) ports on the side

# SPECIFICATIONS

<b>END-TIDAL CARBON DIOXIDE (EtCO<sub>2</sub>)</b>	<b>ENVIRONMENTAL</b>
<b>Range</b>	Operating Temperature . . . . . 32°F to 122°F (0°C to 50°C)
FiCO <sub>2</sub> . . . . . 0 to 15 vol%	Storage Temperature . . . . . -40°F to 158°F (-40°C to 70°C)
EtCO <sub>2</sub> . . . . . 0 to 15 vol%	Operating Humidity . . . . . <4 kPa H <sub>2</sub> O, Non-Condensing (95% RH at 30°C)
RR . . . . . 0 to 150 bpm	Storage Humidity . . . . . 5 to 100% RH, Condensing (100% RH at 40°C)
<b>Accuracy*</b>	<b>PHYSICAL CHARACTERISTICS</b>
FiCO <sub>2</sub> . . . . . ± (0.2 vol% + 2% of reading)	Weight . . . . . 4.5 oz (130 g) including cable
EtCO <sub>2</sub> . . . . . ± (0.2 vol% + 2% of reading)	Dimension . . . . . 1.3 in x 3.1 in x 1.9 in
RR . . . . . ± 1 bpm	<b>SAMPLING LINES</b>
	Water Handling . . . . . Sampling line with proprietary water removal tubing
	Samplig Flow Rate . . . . . 50 ± 10 ml/min with 2 m Nomline sampling line

\*The following accuracy specifications are valid for dry single gases at 22 ± 5 °C and 1013 ± 40 kPa.

**Caution: Federal law restricts this device to sale by or on the order of a physician.**